

DESCRIZIONE / Description

- Spellatubi elettrica ad utensile regolabile con spine di guida, ideale per spellatura di tubi oleodinamici fino a 2”.
- *Dénudeuse électrique avec outil réglable et broches de guidage, idéal pour dénuder les tuyaux hydrauliques jusqu'à 2”.*

SR (esterno - ext)



SCHEDA TECNICA / Fiche Technique

Capacità di spellatura / Capacité de dénudage	2”**
Motore / Moteur	Kw.0.55 (0,75Hp) - 400V- 50/60Hz
Dimensione LxPxH / Dimensions LxIxH	620x520x540mm (24,41”x20,47”x21,26”)
Peso / Poids	55 Kg (121,25 Lbs)

SRI (esterno/interno - ext/int)






SCHEDA TECNICA / Fiche Technique

Capacità di spellatura / Capacité de dénudage	2”**
Motore / Moteur	Kw.0.55 (0,75Hp) - 400V- 50/60Hz
Dimensione LxPxH / Dimensions LxIxH	620x520x540mm (24,41”x20,47”x21,26”)
Peso / Poids	55 Kg (121,25 Lbs)

= di serie / de série

ACCESSORI / Accessoires

<input type="checkbox"/>  Utensile doppio per spellatura esterna <i>Outil double pour le dénudage extérieur</i>	<input type="checkbox"/>  Base portautensili (300x300x190mm) <i>Support porte-outil (11,81x11,81x7,78inch)</i>	<input type="checkbox"/>  Voltaggio speciale <i>Tension spéciale</i>
---	--	--

Spine Spellatrici - Int/Ext / Outils de dénudage - Int/Ext

Ø Tubo / Ø Tuyau		1/4”	5/16”	3/8”	1/2”	5/8”	3/4”	1”	1.1/4”	1.1/2”	2”
Spine Est. / Outils Ext.	R1/R2	X	X	X	X	X	X	X	X	X	X
	4SP/4SH				X	X	X	X	X	X	X
	Interlock						X	X	X	X	X
Spine Int. / Outils Int.	Interlock						X	X	X	X	X