

DESCRIZIONE / Description

- Pressa con touch-screen e encoder centesimale per tubi flessibili oleodinamici fino a 3" 4SP.
- Crimping machine with touch-screen and centesimal encoder for 4SP flexible hydraulic hoses up to 3".
- Presse avec écran tactile et encodeur centesimal pour tuyaux hydrauliques flexibles jusqu'à 3" 4SP.



SCHEDA TECNICA / Data Sheet/ Fiche Technique

Forza di pressatura / Crimping force / Force de sertissage	350 Ton (385,8 US TONS)
Range di pressatura / Operating range / Plage de sertissage	6,5-164mm (0,25"-6,46")
Diametro di pressatura max / Max crimping range / Diamètre de sertissage max.	178mm** (7")
Tubo 6 spirali / 6 spirals hose / Tuyau 6 nappes	2.1/2"
Tubo 4 spirali / 4 spirals hose / Tuyau 4 nappes	3"
Tubo 2 trecce / 2 braids hoses / Tuyau 2 tresses	3"
Tubo industriale / Industrial hose / Tuyau industriel	6"
Velocità chiusura / Close speed / Vitesse de fermeture	33mm/sec (65mm/sec^)
Velocità pressatura / Crimp speed / Vitesse de sertissage	2,2mm/sec
Velocità apertura / Open speed / Vitesse d'ouverture	44mm/sec
Apertura max con morsetti / Max opening with dies / Ouverture max avec mors	+115mm (4,53")
Diametro max di apertura / Max opening without dies / Diamètre d'ouverture max sans mors	283mm (11,14")
Motore / Power / Moteur	7,5kw (10Hp)
Voltaggio Standard / Standard voltage / Tension normale	400V-50/60Hz
Dimensione LxPxH / Dimensions LxWxH	760x850x1710mm (29,92"x33,46"x67,32")
Peso senza olio / Weight without oil / Poids sans huile	1480 Kg (3262 Lbs)
Olio / Oil / Huile	70 L

✓ = di serie / standard / de série

✓ Goniometro per orientamento raccordi /
Goniometer for orientation/ Goniomètre pour
orientation raccords



✓ Morsetto fisso a ore 06:00 / Fixed
clamp at 06:00 o'clock / Mors fixe à 6
heures



ACCESSORI / Accessories / Accessoires

	☐ Pedale elettrico Electric pedal Pédale électrique		☒ Doppia velocità Double speed Vitesse double		☒ Controllo ED con Touch Screen da 10" ED control with 10" touch screen Commande ED avec écran tactile 10"
	☒ Macchina silenziosa Silent machine Machine silencieuse		☒ Specchio retrovisore Rearview mirror Rétroviseur		☒ Illuminazione della zona di lavoro Lighting of the working area Éclairage de la zone de travail
	☐ Telecamera Camera Caméra		☐ Morsetti freni freon, marcatori e speciali Brakes, air conditioning dies marking dies Mors de frein, d'air conditionné, marqua- ge et spéciaux		☐ Battuta posteriore automatica Automatic rear stop Arrêt arrière automatique
	☐ Kit industria 5.0 Industry 5.0 kit Kit Industrie 5.0		☐ Barcode scanner Barcode scanner bluetooth Lecteur de barres-codes		☐ Lubrificazione Automatica Automatic lubrication Lubrification automatique
	☐ Dispenser frontale Frontal dispenser Panneau frontal		☐ Multistep Multistep Multistep		☐ Impugnatura cambio/rapido alluminio Aluminium Quick change handle Changement rapide / poignée en aluminium
	☐ Voltaggio speciale Special voltage Tension spéciale		☐ Controllo forza crimpatura Crimp force control Contrôle force de sertissage		☐ Controllo forza e qualità Force and quality control Contrôle de la force et de qualité

MORSETTI / Dies / Mors

Ø (mm)	6.5	10	13	14	16	18	19	21	22	25	26	30	35	40	45	51	57	63	69	74	78	84	92	100	108	116	120	126	136	146	150	
L (mm)	60	60	60	60	90	90	90	90	90	90	90	90	90	90	90	100	100 120	100 120	105 120	105 120	105 120	120	120	120	120	120	120	120	120	120	120	120

* Valore indicativo in funzione del prodotto da pressare/Indicative value depending on the product which needs to be crimped/Valeur indicative en fonction du produit à sertir
Senza cambio rapido/Without quick change/Sans changement rapide *Con barriere di sicurezza/With safety barrier/Avec barrières de sécurité ** Con porta morsetti/With die holder/Avec porte-matrice