

DESCRIZIONE / Description

- Pressa con comandi elettrici e indicatore di quota analogico per tubi flessibili oleodinamici fino a 3" R2.
- Crimping machine with electrical control and analog measuring micrometer for R2 flexible hydraulic hoses up to 3".
- Presse à commandes électriques et indicateur de hauteur analogique pour flexibles hydrauliques jusqu'à 3" R2.



SCHEDA TECNICA / Data Sheet / Fiche Technique

Forza di pressatura / Crimping force / Force de sertissage	380Ton (419 US TONS)
Range di pressatura / Operating range / Plage de sertissage	6,5-136mm (0,25"-5,35")
Diametro di pressatura max / Max crimping range / Diamètre de sertissage max.	148mm** (5,82")
Tubo 6 spirali / 6 spirals hose / Tuyau 6 nappes	2"
Tubo 4 spirali / 4 spirals hose / Tuyau 4 nappes	2.1/2"
Tubo 2 trecce / 2 braids hoses / Tuyau 2 tresses	3"
Tubo industriale / Industrial hose / Tuyau industriel	4"
Velocità chiusura / Close speed / Vitesse de fermeture	25,3mm/sec
Velocità pressatura / Crimp speed / Vitesse de sertissage	1,6mm/sec
Velocità apertura / Open speed / Vitesse d'ouverture	19,6mm/sec
Apertura max con morsetti / Max opening with dies / Ouverture max avec mors	+54mm (2,13")
Diametro max di apertura / Max opening without dies / Diamètre d'ouverture max sans mors	190mm (7,48")
Motore / Power / Moteur	5,5kw (7,5Hp)
Voltaggio Standard / Standard voltage / Tension normale	400V-50/60Hz
Dimensione LxPxH / Dimensions LxWxH	760x620x900mm (29,92"x24,41"x35,43")
Peso senza olio / Weight without oil / Poids sans huile	420 kg (925,94 Lbs)
Olio / Oil / Huile	60 L

✓ = di serie / standard / de série

ACCESSORI / Accessories / Accessoires

	☐ Pedale elettrico Electric pedal Pédale électrique		☒ Doppia velocità Double speed Vitesse double		☒ Controllo "EL" "EL" Control Contrôle "EL"
	☒ Macchina silenziosa Silent machine Machine silencieuse		☒ Regolazione riapertura automatica testa di pressatura Automatic opening adjustment Réglage automatique de la réouverture de la tête de sertissage		☐ Telecamera Camera Caméra
	☐ Impugnatura cambio/rapido alluminio Aluminium Quick change handle Changement rapide / poignée en aluminium		☐ Morsetti speciali Special dies Mors spéciaux		☐ Battuta posteriore automatica Automatic rear stop Arrêt arrière automatique
	☐ Base dispenser modulare Modular base dispenser Panneau de rangement portable		☐ Morsetti marcatori Marking dies Mors marquage		☐ Battuta posteriore fissa Fixed rear stop Butée arrière fixe
	☐ Voltaggio speciale Special voltage Tension spéciale		☐ Morsetti freni e aria condizionata Brakes and air conditioning dies Mors de freinage et d'air conditionné		
	☐		☐		

MORSETTI / Dies / Mors

Ø (mm)	6.5	10	13	14	16	18	19	21	22	25	26	30	35	40	45	51	57	63	69	74	78	84	92	100	108	116	120	126#	136**
L (mm)	60	60 90	60 90	70 90	70 90	70 90	70 90	70 90	70 90	70 90	70 90	70 90	70 90	90	90	100 120	100 120	100 120	105 120	105 120	105 120	105 120	120	120	120	120	120	120	

* Valore indicativo in funzione del prodotto da pressare/Indicative value depending on the product which needs to be crimped/Valeur indicative en fonction du produit à serrer ** Con porta morsetti/With die holder/Avec porte-matrice
Senza cambio rapido/Without quick change/Sans changement rapide