

DESCRIZIONE / Description

- Spellatubi elettrica ad utensile regolabile con spine di guida, ideale per spellatura di tubi oleodinamici fino a 2".
- Electric hose skiver with adjustable tool with guidance pins, perfect for hose skiving for hydraulic hoses up to 2".
- Dénudeuse électrique avec outil réglable et broches de guidage, idéal pour dénuder les tuyaux hydrauliques jusqu'à 2".

SR (esterno - ext)



SCHEMA TECNICA / Data Sheet / Fiche Technique

Capacità di spellatura / Skiving capacity / Capacité de dénudage 2"

Motore / Power / Moteur Kw.0.55 (0,75Hp) - 400V- 50/60Hz

Dimensione LxPxH / Dimensions LxWxH 620x520x540mm (24,41"x20,47"x21,26")

Peso / Weight / Poids 55 Kg (121,25 Lbs)

SRI (esterno/interno - ext/int)



SCHEMA TECNICA / Data Sheet / Fiche Technique

Capacità di spellatura / Skiving capacity / Capacité de dénudage 2"

Motore / Power / Moteur Kw.0.55 (0,75Hp) - 400V- 50/60Hz

Dimensione LxPxH / Dimensions LxWxH 620x520x540mm (24,41"x20,47"x21,26")

Peso / Weight / Poids 55 Kg (121,25 Lbs)

☒ = di serie / standard / de série

ACCESSORI / Accessories / Accessoires

☐ Utensile doppio per spellatura esterna Double tool for external skiving Outil double pour le dénudage extérieur	☐ Base portautensili (300x300x190mm) Tool base (11,81x11,81x7,78inch) Support porte-outils (11,81x11,81x7,78inch)	☐ Voltaggio speciale Special voltage Tension spéciale
--	--	--

Spine Spellatrici - Int/Est / Hose Skiver Plugs - Int/Est / Outils de dénudage - Int/Ext

Ø Tubo / Ø Hose / Ø Tuyau		1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
Spine Est. / Plugs Est. / Outil Ext.	R1/R2	X	X	X	X	X	X	X	X	X	X
	4SP/4SH				X	X	X	X	X	X	X
	Interlock						X	X	X	X	X
Spine / Plugs / Outil Int.	Interlock						X	X	X	X	X