

## DESCRIZIONE / Description

- Testa di pressatura, compatta e leggera per raccordare tubi flessibili oleodinamici fino a 3/4" R2.
- Crimping head, compact and light, ideal for hydraulic hoses up to 3/4" R2.
- Tête de sertissage compacte et légère pour raccorder des flexibles hydrauliques jusqu'à 3/4" R2.

## SCHEDA TECNICA / Data Sheet/ Fiche Technique

Forza di pressatura / Crimping force / Force de sertissage	60Ton (66,13 US TONS)
Range di pressatura / Operating range / Plage de sertissage	6,5-39mm (0,25"-1,53")
Diametro di pressatura max / Max crimping range / Diamètre de sertissage max.	55mm** (2,16")
Tubo 4 spirali / 4 spirals hose / Tuyau 4 nappes	-
Tubo 2 trecce / 2 braids hoses / Tuyau 2 tresses	3/4"
Tubo industriale / Industrial hose / Tuyau industriel	1"
Apertura max con morsetti / Max opening with dies / Ouverture max avec mors	+20mm (0,79")
Diametro max di apertura / Max opening without dies / Diamètre d'ouverture max sans mors	59mm (2,32")
Dimensione LxPxH / Dimensions LxWxH	200x320x330mm (7,87"x12,6"x13")
Peso / Weight / Poids	11 Kg (24,25 Lbs)



✓ = di serie / standard / de série

## ACCESSORI / Accessories / Accessoires

<input checked="" type="checkbox"/>	Nonio graduato per regolazione Ø di pressatura Analog measuring micrometer Vernier gradué pour pressage réglage Ø	<input type="checkbox"/>	Morsetti speciali Special dies Mors spéciaux	<input type="checkbox"/>	Morsetti aria condizionata Air conditioning dies Mors air conditionné
<input type="checkbox"/>	Morsetti freno Brakes dies Mors de frein	<input type="checkbox"/>	Pedale pneumo-idraulico Pneumo-hydraulic pedal Pédale hydro-pneumatique	<input type="checkbox"/>	Pompa a mano doppio stadio Two-stage manual pump Pompe à main à deux vitesses
<input type="checkbox"/>	Dispenser portatile Portable dispenser Panneau rangement portable	<input type="checkbox"/>	Pompa a batteria Battery pump Pompe à batterie	<input type="checkbox"/>	Base di supporto con portamorsetti integrato Support base with integrated dies support Base de soutien avec support à mors intégré
<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	

## MORSETTI / Dies / Mors

Ø (mm)	6.5	10	13	16	19	22	26	30	39**											
L (mm)	55	55	55	55	55	55	65	65												

\* Valore indicativo in funzione del prodotto da pressare/Indicative value depending on the product which needs to be crimped/Valeur indicative en fonction du produit à sertir \*\* Con porta morsetti/With die holder/Avec porte-matrice