

DESCRIZIONE / Description


- Testa di pressatura, compatta e leggera, per raccordare tubi flessibili oleodinamici fino a 1" R2.
- *Crimping head, compact and light, ideal for hydraulic hoses up to 1" R2.*
- *Tête de sertissage compacte et légère, pour raccorder des flexibles hydrauliques jusqu'à 1" R2.*

**SCHEMA TECNICA / Data Sheet / Fiche Technique**

Forza di pressatura / Crimping force / Force de sertissage	100Ton (110,23 US TONS)
Range di pressatura / Operating range / Plage de sertissage	6,5-39mm (0,25"-1,53")
Diametro di pressatura max / Max crimping range / Diamètre de sertissage max.	55mm** (2,16")
Tubo 4 spirali / 4 spirals hose / Tuyau 4 nappes	3/4**
Tubo 2 trecce / 2 braids hoses / Tuyau 2 tresses	1**
Tubo industriale / Industrial hose / Tuyau industriel	1**
Apertura max con morsetti / Max opening with dies / Ouverture max avec mors	+20mm (0,79")
Diametro max di apertura / Max opening without dies / Diamètre d'ouverture max sans mors	59mm (2,32")
Dimensione LxPxH / Dimensions LxWxH	200x320x330mm (7,87"x12,6"x13")
Peso / Weight / Poids	21 Kg (46,3 Lbs)

☒ = di serie / *standard* / de série

ACCESSORI / Accessories / Accessoires

Accessories		
☒  Nonio graduato per regolazione Ø di pressatura Analog measuring micrometer Vernier gradué pour pressage réglage Ø	☐  Morsetti aria condizionata Air conditioning dies Mors air conditionné	☐  Morsetti speciali Special dies Mors spéciaux
☐  Morsetti freno Brakes dies Mors de frein	☐  Pedale pneumo-idraulico Pneumo-hydraulic pedal Pédale hydro-pneumatique	☐  Pompa a mano doppio stadio Two-stage manual pump Pompe à main à deux vitesses
☐  Dispenser portatile Portable dispenser Panneau rangement portable	☐  Pompa a batteria Battery pump Pompe à batterie	☐  Base di supporto con portamorsetti integrato Support base with integrated dies support Base de soutien avec support à mors intégré
☐	☐	☐
☐	☐	☐
☐	☐	☐

MORSETTI / Dies / Mors

[illegible]

* Valore indicativo in funzione del prodotto da pressare/Indicative value depending on the product which needs to be crimped/Valeur indicative en fonction du produit à sertir ** Con porta morsetti/With die holder/Avec porte-matrice